

SEWOO has POS printer line to suit for point of sales application and needs in marketplace.

SLK-TS400

- Compact size
- Top & Front exit available
- Easy Replacement of Components (Tool-less)
- ESC/POS command compatible
- Jam free design -
- Wall mount installation available



Application

RETAIL



SUPERMARKET

DEPARTMENT STORE

COSMETIC STORE

HOSPITALITY



HOTEL

AIRPORT

RESTAURANT

TICKET



AMUSEMENT PARK TICKET

ADMISSION TICKET

ENTRANCE TICKET

LOTTERY



COUPON



DAILY REPORT



3INCH THERMAL PRINTER

SLK-TS400

PRINTING SPECIFICATION

PRINTING

METHOD	Direct Thermal
SPEED	220mm/sec
WIDTH	72mm
RESOLUTION	180 DPI

BARCODE

1D	Code 11, Code39, Code 93, Codebar, IASBT-128, UPC-A, UPC-E, EAN-8, EAN-13, Code128 with subsets A/B/C, Interleaved 2-of-5
2D	PDF417, QR Code, DATA MATRIX

PAPER SPECIFICATION

TYPE	Receipt
WIDTH	80mm
THICKNESS	0.065mm
ROLL DIAMETER	Ø 83mm

INTERFACE



STANDARD	USB
OPTION	Serial(RS-232C, 25pin), Ethernet

HARDWARE SPECIFICATION

POWER

TYPE	External SMPS
AC	100 ~ 240Vac 50/60 Hz
DC	24Vdc / 1.75A

SENSOR

Paper End, Cover Open


RELIABILITY

TPH LIFE	150Km
AUTO CUTTER	1,500,000 cuts(Guillotine)

CASH DRAWER

DKD (Cash Drawer) 1Port

• All specification and designs are subject to change without notice.



DRIVER

Windows Driver(2012, 8, 7, 2008, VISTA, 2003, XP, 32bit & 64bit), Windows CE & Mobile Driver & SDK(CE 4.2 ~, Mobile 5.0 ~), Linux Driver, Mac Driver, OPOS Driver, JavaPOS Driver, iOS SDK, Android(2.1 ~) SDK, Windows SDK

EMULATION

ESC/POS Command compatible

ACCESSORIES (OPTION)

Melody Box, Wall Mount

DIMENSION

W x D x H	130 x 140 x 154 (mm)
-----------	----------------------

KEY FEATURES

COMPACT SIZE

The Comparison of size between SLK-TS400 and Smartphone



TOP EXIT



FRONT EXIT



*Front exit is available with a wall mounted.



SEWOO TECH CO.,LTD.

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 447-210 Republic of Korea

TEL +82-31-8077-5000 FAX +82-31-459-8880

E-Mail : sales@miniprinter.com

